



















## Mullion based wall systems

## Fully-glazed wall systems

## Post-and-beam

Mullion based wall systems					Fully-glazed wall systems			Post-and-beam	Design								
System 2000	System 2000_Nature	System 2300	System 2000_Nature	System 2300	System 3400	System 3400_Plus	System 3500	System T	Partition wall system								
Demountable modular partition wall system based on the patented Straehle steel mullion with variable panelling and high sound and fire ratings. A wide range of door solutions supplement the system.					Wooden version of the System Family 2000 with real wood profiles and a flush-mounted design.		Structural glazing variant of the system 2000 family with flush glazed aesthetic including the system frames and door leaves.		Variable fully-glazed wall system without mullions with single layer glazing for maximum transparency.		Single-shell all-glass construction with vertical and horizontal partitions.		Double-glazed framed wall system without mullions for maximum transparency.		Timber based post-and-beam partition wall system with flush glazing fastened via stainless steel fixings.		Description
Solid wall	Central glazing	Flush glazing	Flush glazing	Structural-Glazing	Glass wall	Glass wall	Glass wall	Glass wall, Solid wall	Detail								
									Photographic detail								
									Finish Surface/Material								
Melamine, veneer, HPL or laquered, metall panels, absorber elements	Single glazing with toughened / laminated glass or insulating glass	Double glazing or single glazing possible with toughened / laminated glass	Double glazing with toughened / laminated glass	Double glazing or single glazing possible with toughened / laminated glass	Variable single glazing section for 10-16 mm, toughened / laminated glass	Variable single glazing section for 10-16 mm, toughened / laminated glass	Double glazed partion with 10 or 12 mm toughened / laminated glass	Double glazing 6 or 8 mm toughened / laminated glass	Element types								
solid wall Transverse subdivision to choice	All-glass, Toplight, Balustrade	All-glass, Toplight, Balustrade	All-glass, Toplight, Balustrade	All-glass, Toplight, Balustrade	All-glass ceiling-high	All-glass ceiling-high or with subdivisions	All-glass ceiling-high	All-glass, Toplight, Balustrade, Solid wall	Wall thickness								
100/125 mm, Sonderausführung 160 mm	100/125 mm	100/125 mm	100 mm	100/125 mm	22-40 mm	40-50 mm	100 mm	100 mm	Sound insulation								
R <sub>w,P</sub> 45-56 dB, Special version 57 dB	R <sub>w,P</sub> 32-42 dB,	R <sub>w,P</sub> 30-52 dB (Special version till 54 dB)	R <sub>w,P</sub> 42-52 dB	R <sub>w,P</sub> 42-54 dB	R <sub>w,P</sub> 32-40 dB	R <sub>w,P</sub> 32-40 dB	R <sub>w,P</sub> 40-47 dB	R <sub>w,P</sub> 41-48 dB	Fire rating								
F 30/F 90	F 30	F 30	-	F 30	-	-	-	-	Special elements								
Acoustic absorption elements Climate control elements, Organisational accessories	Acoustic absorption elements Climate control elements, Organisational accessories, Blinds	Acoustic absorption elements Climate control elements, Organisational accessories, Blinds	Acoustic absorption elements Climate control elements, Organisational accessories, Blinds	Acoustic absorption elements Climate control elements, Organisational accessories, Blinds	Acoustic absorption elements	Acoustic absorption elements Whiteboards, Organisational accessories	-	Acoustic absorption elements Climate control elements, Blinds									